



To : Mr. Oliver M. Filoteo  
Chief Executive Officer  
From : Quality Control Department  
Re : Split type air-conditioner  
Date : December 12, 2024  
Reference no. : QCD-SAC-10IDAH-I -24-12-001  
Cc. : FDF. / A De Rivera /Dept. concern


Listed below are the specifications and parts for the new model of Versa match Multi Split type air conditioner, received and inspected this December 09, 2024.

**KVM-10IDAH-I (1.0hp) (Versa Match)**  
**INDOOR UNIT**

**Details checking:**

**Model** : KVM-10IDAH-I  
**Description** : 1.0hp Ceiling Concealed Inverter Versa match Air-con.  
**EAN Number** : 4 806508 236288  
**P/O Number** : KT-2407GR-18  
**Lot number** : 157224001  
**Serial number range** : 15722407-10001 to 10005 (5 units)  
**Printing Features** : Good, clear, and correct

**Inspected units:** **Kolin Serial number** 15722407-10005, 10003, 10004 and 10001  
**Supplier Serial no.** 9CM7140000006, 00004, 00005 and 00002



**Remarks:**

First shipment for new model of multi split type inverter VERSA MATCH series. The carton box packaging dimensions, and specs are based on approved designed. The internal parts inspected are based on the actual unit.

**Recommendations:**

1. For rework to attach the QR code on warranty card.
2. For internal performance, functional and life testing.

**Note:** All details and specifications reported are based on the actual unit inspected, And supplier's spec's sheets, no sample unit for the comparisons.

### Packaging and Carton box checking:

<b>Packaging Dimensions:</b>	W x D x H Gross weight	1008 x 568 x 275mm 22.5 kg.
<b>Carton Box Dimensions:</b>	W x D x H / Weight: Type / Thickness:	1000 x 570 x 269mm / 1745 grams Double wall, BC flute / 6.0mm
<b>Packaging Support:</b>	Right side support: Left side support: Top support: Bottom support: Carton base:	Carton / Thickness: 25mm / 0.495g. Carton / Thickness: 25mm / 0.305g. Carton / Thickness: 25mm / 0.165g. Carton / Thickness: 30mm / 0.425g. Double wall, BC flute / 6.0mm 988 x 522 x 100mm / 0.800g.
<b>Accessories:</b>	Owner's Manual, Wired control manual, Warranty card Display wired controller, Controller cable (8000mm length) Controller holder, Screw (2pcs) Insulation foam (2pcs.) Pipe insulation sheath (2pcs. / 158mm length) Clip on ring Ø9mm and Ø6mm Installation nut (4 pcs.), Cable ties (8pcs) Lock washers (4pcs.) Nut with washers Flare nut, nut Ø1/4 and Ø3/8	

### Unit checking for outer part:

<b>Specifications</b>	Phase	Single
	Volts	230 V~
	Frequency	60Hz
	Nominal Capacity	1.0hp
	Cooling Capacity	9,495 kJ/h 2.64kW
	Max Discharge Pressure	4.3 MPa
	Max Suction Pressure	2.5 MPa
	Fan Motor Power Input	50 Watts / 1.0 Amperes
	Moisture Protection	IPX0
	Sound Pressure level	28 dB(A) High
	Refrigerant type	R 32
Refrigerant Piping	1/4" & 3/8"	
<b>Unit Dimension</b>	W x D x H Net weight	710 x 450 x 200mm 18.5 kg
<b>Appearance</b>	Galvanized coated casing with orange sticker KOLIN logo. Transferable air intake panel back and bottom.	
<b>Kolin Logo</b>	Color / Dimensions (W x H)	Orange / 81 x 28mm
<b>Air Filter</b>	Color / Dimensions	Green and Black / 345 x 189mm

**Unit checking for inner part:**

<b>Blower Fan Motor:</b>	Type: Model: Part number: Specifications:  Manufacturer: Appearance:	Fan A synchronism motor for Air conditioner YSK20-4U (FG20H) 1570520106 220-240V~ 50Hz / 208-230V~ 60Hz / 20W 0.35A / 1000 r/min / 4P/ IP20 Zhuhai Kaibang Motors Galvanize coated casing
<b>Control Module:</b>	<b>FM Capacitor:</b>	2 $\mu$ f $\pm$ 5% 450VAC / 50-60Hz CBB61
	<b>Main PCB:</b>	300002061990 / Z4L1512CJ GRZ4M-A4 (V1) 2022/07/24/12 T1.6
	<b>Wired Remote Control:</b>	300001060893 / K79941 / Z4M3511AJ GRZ4M-B (V1) 2023 / 09 / 09 / 11 T1.6
	<b>Drain Pump</b>	DP-12230 / 812007060016 208-230V / 50-60Hz / 9.4W / 8W Zhejiang Fuji Seiko Technology
	<b>Control Box:</b>	GI and Plastic materials
<b>Unit Sensor:</b>	Temperature / Tubing	GL/GW 15K / GL/GW 20K
<b>Evaporator:</b>	Aluminum fins: Copper tubing: Dimensions:	408pcs. Blue Aluminum fins 2 rows of 24 lines with $\varnothing$ 5.0mm each (L x H x W) 547 x 228 x 23mm
<b>Copper tube:</b>	High side / Low side	$\varnothing$ 1/4" and $\varnothing$ 3/8" with flare cover (plastic)
<b>Wheel blower :</b>	Appearance: Dimension:	Yellowish color / ABS Plastic materials $\varnothing$ 144mm x 143mm (2pcs.)
<b>Blower housing:</b>	Appearance: Dimension:	Yellowish color, plastic materials (2pcs.) 229 x 207 x 203mm
<b>Drain pan:</b>	Appearance: Dimension:	Styrofoam and, plastic materials 696 x 268 x 57mm

**Unit inner part / spec's**

	<p style="text-align: center;"><b>FAN MOTOR</b></p> <p style="text-align: center;">YSK20-4U (FG20H) 1570520106 220-240V~ 50Hz / 208-230V~ 60Hz / 20W</p>
---	--



### FM CAPACITOR

2 $\mu$ f  $\pm$ 5% 450VAC / 50-60Hz CBB61



### MAIN PCB

300002061990 / Z4L1512CJ  
GRZ4M-A4 (V1) 2022/07/24/12 TL.6




### DRAIN PUMP

DP-12230 / 812007060016  
208-230V / 50-60Hz / 9.4W / 8W




### WIRE REMOTE CONTROL

300001060893 / K79941  
Z4M3511AJ



### EVAPORATOR

Blue Aluminum fins  
2 rows of 24 lines with  $\varnothing$ 5.0mm each  
(L x H x W) 547 x 228 x 23mm

	<p style="text-align: center;"><b>COPPER TUBING</b></p> <p style="text-align: center;">Ø1/4" and Ø3/8" with flare cover</p>
	<p style="text-align: center;"><b>BLOWER WHEEL</b></p> <p style="text-align: center;">Yellowish color, plastic materials (2pcs.) Ø144mm x 143mm</p>
	<p style="text-align: center;"><b>ACCESSORIES</b></p> <p>Owner's Manual, Wired control manual, Warranty card Display wired controller, Controller cable (8000mm length) Controller holder, Screw (2pcs) Insulation foam (2pcs.) Pipe insulation sheath (2pcs. / 158mm length) Clip on ring Ø9mm and Ø6mm Installation nut (4 pcs.), Cable ties (8pcs) Lock washers (4pcs.) Nut with washers Flare nut, nut Ø1/4 and Ø3/8</p>

For your reference,

Prepared by : Jayson L. Pagacita  
Quality Control Staff

Noted by : Alberto I. Francisco  
QC, Asst. Supervisor

Approved by : Mr. Fernando D. Feliciano  
Plant Operations Manager