



To : ALL DEPARTMENT
 From : Sales Supervisor
 Date : February 26, 2024
 Subject : NEW PRODUCT –
 CEILING CASSETTE INVERTER AND FLOOR CEILING INVERTER (4HP AND 6HP)
 Ref : SAL-SUP-24-2- 122
 CC : DCO, File

This is to formally introduce our new product “Ceiling Cassette Inverter and Floor Ceiling Inverter (4hp and 6hp)” which will be available for ordering on March 1, 2024 with details below:

PRODUCT PICTURE	SPECS	**FLOOR CEILING**	
		KLM-IC40-AA1M32	KLM-IC60-AA1M32
	SRP	Php 117,995	Php 151,995
	Ordering Date:	March 1, 2024	
	Nominal Capacity	3TR/ 4.0HP	5TR/ 6.0HP
	Cooling Capacity	37,980 (11,394-41,778)kJ/h	55,503 (15,562-60,346)kJ/h
	Power Supply	1 Ph/ 230V/ 60Hz	1 Ph/ 230V/ 60Hz
	Rated Current	15A	25A
	Rated Power	3,184 (637-3,821) W	5,306 (1,061-6,367) W
	CSPF Rating	4.92	-
	Star Rating	★★★★★	-
	Airflow (Hi/Mi/Lo)	1,900/1,600/1,400 m³/h	2,400/2,100/1,900 m³/h
	Sound Level (Hi/Mi/Lo)	55/51/47 dB(A)	57/54/52 dB(A)
	Unit Dimension (WxDxH)	1,285 x 675 x 235 mm	1,650 x 675 x 235 mm
	Package Dimension (WxDxH)	1,360 x 755 x 318 mm	1,725 x 755 x 318 mm
	Unit Weight (Net/Gross)	32/ 38g	42/ 49.1g
	Refrigerant Type/Charge	R32 / 1,450g	R32 / 2,650g
	Area (Unloaded Space)	65 m²	96 m²
FEATURES			
* 5-Star Rating (4.0hp) * 3D Air Flow (vertical or horizontal) * Versatile Installation(Ceiling or Floor) * Self-Diagnosis * Inverter Technology * Quiet Operation: as low as 43dB(A) * R32 Refrigerant			

PRODUCT PICTURE	SPECS	**CEILING CASSETTE**	
		KLM-IS40-AA1M32	KLM-IS60-AA1M32
	SRP	Php 119,995	Php 154,995
	Ordering Date:	March 1, 2024	
	Nominal Capacity	3TR/ 4.0HP	5TR/ 6.0HP
	Cooling Capacity	37,980 (11,394-41,778)kJ/h	55,503 (15,562-60,346)kJ/h
	Power Supply	1 Ph/ 230V/ 60Hz	1 Ph/ 230V/ 60Hz
	Rated Current	15A	25A
	Rated Power	3,184 (637-3,821) W	5,306 (1,061-6,690) W
	CSPF Rating	5.24	-
	Star Rating	★★★★★	-
	Airflow (Hi/Mi/Lo)	1,950/1,700/1,500 m³/h	2,100/1,800/1,500 m³/h
	Sound Level (Hi/Mi/Lo)	56/52/48 dB(A)	55/51/47 dB(A)
	Unit Dimension (WxDxH)	830 x 830 x 245 mm	830 x 830 x 287 mm
	Package Dimension (WxDxH)	910 x 910 x 290 mm	910 x 910 x 330 mm
	Front Panel Dimension (WxDxH)	950 x 950 x 55 mm	950 x 950 x 55 mm
	Unit Weight (Net/Gross)	27.8/ 32.7g	29.8/ 35.1g
	Refrigerant Type/Charge	R32 / 1,450g	R32 / 2,650g
	Area (Unloaded Space)	65 m²	96 m²
FEATURES			
*5-Star Rating (4.0hp) *360° Air Flow/Discharge *Built-In Drain Pump *Self-Diagnosis * Inverter Technology * Quiet Operation: as low as 47dB(A) * R32 Refrigerant			

SPECS	**FLOOR CEILING AND CEILING CASSETTE OUTDOOR UNITS**	
	KLM-IX40-AA1M32	KLM-IX60-AA1M32
Ordering Date:	March 1, 2024	
Unit Dimension (WxDxH)	890 x 342 x 673 mm	946 x 410 x 810 mm
Package Dimension (WxDxH)	995 x 435 x 750 mm	1,090 x 500 x 885 mm
Unit Weight (Net/Gross)	43.9/ 47.1g	63.9/ 68.9g
Copper Tube (High Side/ Low Slide)	ø 3/8 / ø 5/8"	ø 3/8 / ø 5/8"
Max Pipe Distance Between Indoor and Outdoor (Height/Length/ Circuit Breaker)	20m / 30m / 40A	30m / 50m / 60A
FEATURES		
*Both compatible to Floor Ceiling and Ceiling Cassette with same nominal capacity		
PRODUCT PICTURE		
 KLM-IX40-AA1M32  KLM-IX60-AA1M32		

Please be guided accordingly.

Prepared by:

Joanna Marie E. Dulog
Sales Supervisor

Noted by:

Mr. Christian Keith V. Sarmiento
National Sales Manager

Approved by:

Mr. Oliver M. Floreo
Executive Vice President/COO