

FLOOR STANDING AIRCONDITIONER



KFM-400F1J



KFM-7001E



KFM-400GF1INV / KFM-700HF1INV

FLOOR MOUNTED - INVERTER

FLOOR MOUNTED - REGULAR

FLOOR MOUNTED SPLIT TYPE	KFM-400F1J	KFM-7001E	KFM-400GF1INV	KFM-700HF1INV
Rating Capacity	3 TR	4.5 TR	3 TR	4.5 TR
Cooling Capacity (kJ/h)	37,980	57,596	9,020-41,000	58,025
Area (Unloaded Space)	65 m2	95 m2	70 m2	100 m2
Rated Voltage	1PH/230V / 60 hz	3PH/230V / 60 hz	1PH/230V / 60 hz	3PH/230V / 60 hz
Rated Current (A)	19.5	20	19.5	21
Rated Power (w)	3,900	5,700	725-3,200	6,600
EER	9.7	10.1	12.4-12.8	9
Indoor Unit				
Unit Dimension (WxDxH) (mm)	540 x 410 x 1,825	600 x 350 x 1,900	550 x 330 x 1,800	610 x 390 x 1,925
Net Weight(kg)	56	65	50	59
Outdoor Unit				
Unit Dimension (WxDxH) (mm)	895 x 330 x 860	710 x 710 x 843	990 x 345 x 965	938 x 390 x 1,369
Net Weight(kg)	67	76	71	71
Refrigerant Charge(g)	R-22 / 2,400g	R-22 / 2,400g	R-410a / 2,450g	R-410a / 4,600g
Copper Tube Size				
Hi-pressure	1/2"	1/2"	3/8"	3/8"
Low-pressure	3/4"	3/4"	5/8"	5/8"
Max. Pipe (IU-OU)	30 m	30 m	30 m	30 m
Max. Height (IU-OU)	10 m	10 m	10 m	10 m
Circuit Breaker (A)	40 A	40 A/3PH	40 A	40 A/3PH

* Product features and specifications are subject to change without prior notice

w / 1,000
X How many hrs.
X kw area