

FLOOR CEILING

MODEL	KLM-SC40-4F1M	KLM-SC70-4F3M	KLM-IC40-2C1M
Power Supply	1 PH / 230 V / 60 Hz	3 PH / 230 V / 60 Hz	1 PH / 230 V / 60 Hz
Nominal Capacity	4.0 hp / 3 TR	7.0 hp / 5 TR	4.0 hp / 3 TR
Cooling Capacity	37,982 kJ/h	61,193 kJ/h	11,495 - 37,980 kJ/h
Rated Current	16.1 A	24.3 A	4.8 - 16 A
Rated Power	3703 W	5600 W	1,200 - 3,520 W
EER	10.3 kJ/hW	10.9 kJ/hW	9.6 - 10.8 kJ/hW
Refrigerant (Type/Charge)	R-410A / 2,500 g	R-410A / 4,100 g	R-410a / 2,800 g
INDOOR UNIT			
Airflow (Hi/Mi/Lo)	2432 / 2034 / 1755 m³/h	2626 / 2385 / 2246 m³/h	1900 / 1700 / 1450 m³/h
Sound Level (Hi/Mi/Lo)	56.4 / 51.7 / 47.7 dB(A)	58.1 / 56.0 / 54.6 dB(A)	57 / 54 / 51 dB(A)
Unit Dimension (WxDxH)	1650 x 675 x 235 mm	1650 x 675 x 235 mm	1285 x 675 x 235 mm
Packaging Dimension (WxDxH)	1725 x 755 x 313 mm	1725 x 755 x 313 mm	1360 x 755 x 313 mm
Unit Weight (Net / Gross)	40.9 / 47.6 kg	45.5 / 51.5 kg	30.0 / 35.0 kg
OUTDOOR UNIT			
Unit Dimension	946 x 410 x 810 mm	952 x 415 x 1333 mm	946 x 410 x 810 mm
Packaging Dimension (WxDxH)	1090 x 500 x 875 mm	1095 x 495 x 1480 mm	1090 x 500 x 875 mm
Unit Weight (Net / Gross)	67.2 / 73.0 kg	109.1 / 121.6 kg	69.0 / 75.0 kg
Copper Tube Size			
Low Side	Ø 3/4"	Ø 7/8"	Ø 5/8"
High Side	Ø 3/8"	Ø 3/8"	Ø 3/8"
Maximum Pipe Distance Between Indoor and Outdoor			
Height	10 m	10 m	10 m
Length	30 m	30 m	30 m
Circuit Breaker	40 A	40 A / 3 PH	40 A

***Product features and specifications are subject to change without prior notice

FEATURES FOR FLOOR CEILING

- LED Lights Display Panel
- Left or Right Drain Position
- Outdoor Condenser Type
- Single Louver
- (Side / Top Discharge)

NON-INVERTER

KLM-SC40-4F1M



KLM-SC70-4F3M



INVERTER

KLM-IC40-2C1M



AIR CURTAIN

MODEL	KAC-36RG	KAC-48RG
Power Supply	220 - 230 V 60Hz	220 - 230 V 60Hz
Airflow Volume	1,200 CFM	1,650 CFM
Sound Level	59 dB(A)	61 dB(A)
Rated Power	110 W	140 W
Unit Weight	16.0 kg	20.0 kg
Unit Dimension (WxDxH)	900 x 220 x 220 mm	1,202 x 220 x 220 mm

KAC-36RG KAC-48RG

