

FLOOR MOUNTED

INVERTER KLM-IF70-3D3M KLG-IF70-2C1M KLG-IF40-2C1M



MODEL	KLG-SF40-3D1M	KLG-SF70-4D3M	KLG-IF40-2C1M	KLG-IF70-2C1M	KLM-IF70-3D3M
Power Supply	1 PH / 230 V / 60 Hz	3 PH / 230 V / 60 Hz	1 PH / 230 V / 60 Hz	1 PH / 230 V / 60 Hz	3 PH / 230 V / 60 Hz
Nominal Capacity	4.0 hp / 3 TR	7.0 hp / 5 TR	4.0 hp / 3 TR	7.0 hp / 5 TR	7.0 hp / 5 TR
Cooling Capacity	37,980 kJ/h	54,720 kJ/h	12,945 - 43,150 kJ/h	18,600 - 62,000 kJ/h	19,300 - 64,355 kJ/h
Rated Current	19 A	25 A	4.5 - 15 A	7.5 - 23 A	5.1 - 16.2 A
Rated Power	3850 W	5570 W	1,200 - 3,400 W	1,850 - 5,850 W	1,900 - 5,770 W
EER	9.9 kJ/hW	9.8 kJ/hW	10.79 - 12.7 kJ/hW	10 - 10.6 kJ/hW	10.16 - 11.1 kJ/hW
Refrigerant (Type/Charge)	R-410a / 2,600 g	R-410a / 4,600 g	R-410a / 3,500 g	R-410a / 5,500 g	R-410a / 4,050 g

INDOOR UNIT

Airflow (Hi/Mi/Lo)	1800/1630/1420/1250 m³/h	1800/1630/1420/1250 m³/h	1800/1630/1420/1250 m³/h	1800/1630/1420/1250 m³/h	2200/1950/1580 m³/h
Sound Level (Hi/Mi/Lo)	51 / 49 / 47 / 45 dB(A)	51 / 49 / 47 / 45 dB(A)	52 / 50 / 48 / 46 dB(A)	52 / 50 / 48 / 46 dB(A)	55.8 / 49.2 dB(A)
Unit Dimension (WxDxH)	581 x 395 x 1870 mm	581 x 395 x 1870 mm	580 x 395 x 1870 mm	581 x 395 x 1870 mm	610 x 390 x 1925 mm
Packaging Dimension (WxDxH)	2080 x 735 x 530 mm	2080 x 735 x 530 mm	2080 x 735 x 530 mm	2080 x 735 x 530 mm	2070 x 765 x 515 mm
Unit Weight (Net / Gross)	59.0 / 85.0 kg	59.0 / 85.0 kg	56.0 / 75.0 kg	59.0 / 85.0 kg	59.0 / 77.0 kg

OUTDOOR UNIT

Unit Dimension (WxDxH)	1000 x 427 x 790 mm	1000 x 427 x 1365 mm	1105 x 440 x 1100 mm	1000 x 427 x 1365 mm	952 x 415 x 1333 mm
Packaging Dimension (WxDxH)	1140 x 480 x 865 mm	1135 x 475 x 1385 mm	1155 x 480 x 1115 mm	1135 x 475 x 1385 mm	1095 x 495 x 1400 mm
Unit Weight (Net / Gross)	69.0 / 74.0 kg	126 / 137 kg	92.0 / 100 kg	126 / 137 kg	104 / 116 kg

Copper Tube Size

Low Side	Ø 5/8"	Ø 3/4"	Ø 5/8"	Ø 3/4"	Ø 3/4"
High Side	Ø 1/4"	Ø 1/2"	Ø 3/8"	Ø 3/8"	Ø 3/8"

Maximum Pipe Distance Between Indoor and Outdoor

Height	10 m	10 m	10 m	10 m	10 m
Length	30 m	30 m	30 m	30 m	30 m
Circuit Breaker	40 A	40 A / 3 PH	40 A	60 A	40 A / 3 PH

***Product features and specifications are subject to change without prior notice

FEATURES FOR FLOOR MOUNTED

- Digital LED Display
- Self Diagnostic Error
- Remote Holder
- Side Air Intake
- Auto Louvers
- Energy Saving / Save Energy (SE)
- Living Room Ambient Mode
- Office / Restaurant Ambient Mode
- Common Mode

NON-INVERTER KLG-SF70-4D3M KLG-SF40-3D1M



MODEL	KAC-36RG	KAC-48RG
Power Supply	220 - 230 V 60Hz	220 - 230 V 60Hz
Airflow Volume	1,200 CFM	1,650 CFM
Sound Level	59 dB(A)	61 dB(A)
Rated Power	110 W	140 W

AIR CURTAIN

KAC-36RG KAC-48RG