Installation Program Guideline

- 1. Program covers all purchases of brand new Kolin Wall Mounted Split Type Air Conditioners.
- 2. Presentation of Original Sales Invoice and submission of photocopy is necessary to avail of the installation program.
- 3. Installation program covers first 10 feet of Insulated Copper Tube and labor. In excess of 10 feet, additional charge per foot for insulated copper tube.
- 4. Only Kolin Technicians or its Authorized Service Centers are allowed to install the units for customers to avail of the program.
- 5. Program does not include the following: Royal Cord, Outdoor Unit Bracket, Outdoor Breaker.
 - **Note: Power supply connection from Outdoor breaker to main source and drain line must be supplied by the customer.
- 6. Masonry works (concrete chipping and plastering) is not included and must be supplied by customers.
- 7. Transportation and lodging fees will be charged to customers for installation outside Metro Manila and for Provincial areas outside city limits of Kolin Service Centers.
- 8. P500 will be charged as survey fee; however this is deductible from the Installation charges.





24 °C Digital L.E.D. Display



Precise Settings



Quiet Operation



24 Hour On/Off Timer



Four Way Fan Speed

Model		KSG-100B1G	KSG-150B1G	KSG-200B1G	KSG-250B1G	KSG-300B1F
Cooling Capacity		9497 kJ/h	12660 kJ/h	18990 kJ/h	23760 kJ/h	28487 kJ/h
Area (unloaded space)		12-18 m ²	16-24 m ²	23-34 m ²	32-42m ²	43-49m ²
Rated Voltage		1Ph, 230 Volts, 60 Hz				
Rated Current (A)		4	5.5	8.6	10.2	12.5
Power (W)		900	1200	1870	2200	2826
EER (kJ/hW)		10.5	10.5	10.1	10.8	10.1
ndoor Unit	Net/Gross Weight (kg)	9/12	10/13	13/17	15.5/20.5	17.5/24
	Unit Dimension (WxHxD)(mm)	790x265x170	845x275x180	940x298x200	1007x315x219	1178x338x252
Packing Dimension (WxHxD)(mm)		870x355x248	915x355x255	1010x285x380	1073x313x395	1268x358x420
Dutdoor Unit	Net/Gross Weight (kg)	25/27.5	27/31	37/41	49/54	61/66
,	Unit Dimension (WxHxD)(mm)	720x428x310	810x540x280	848x540x320	955x700x396	980x790x427
Packing Dimension (WxHxD)(mm)		765x475x350	878x580x360	878x580x360	1026x735x455	1083x855x488
Copper Tube	Hi-Pressure	1/4″	1/4"	1/4"	1/4″	1/4″
Size	Low-Pressure	3/8"	1/2"	1/2"	5/8″	5/8"
Max. Distance	Height (m)	5	5	8	8	8
oet. IU & OU	length (m)	10	• 10	15	15	15
Circuit Breaker Requirement (A)		20	20	30	30	30
Refrigerant / Charge		R22 / 690g	R22 / 700g	R22 / 1050g	R22 / 1350g	R22 / 1950g

**Product features and specifications are subject to change without prior notice











HEAD OFFICE

Kolin Bldg. 1854 Sta. Rita St., Guadalupe Nuevo, Makati City, 1212 (632) 852 - 6868

CEBU

Unit #6A. Geson Bldg., D. Jakosalem cor F. Ramos Sts., Cebu City (032) 253 - 9997

PAMPANGA

Mexico Gold Commercial and Residential Building, Jose Abad Avenue, Lagundi Mexico Pampanga (045) 455 - 2934

DAVAO

Door #5 Belle Fran Arcade, E. Palma Git St., Bo. Obrero Davao City (082) 227 - 7063

DAGUPAN

#107 Caranglaan District, Dagupan City (075) 523 - 2832

Julio Pacana St., Puntod,

Cagayan de Oro City

(088) 856 - 4672

BACOLOD

Door #A-2 & A-3 UTC Bldg., Alunan St. Brgy. Singcang, **Bacolod City** (034) 433 - 0031

Door #4, D' Appliance Arcade, South Fundidor, Molo, Iloilo City (033) 336 - 1970

ILOILO

CAGAYAN DE ORO ZAMBOANGA Dr. #3 de Oro Land Bldg.,

Door E Azul Bldg. Don Alfaro St. Tetuan Zamboanga City (062) 992 - 2493



