



HIGH EER



QUICK COOLING



PRECISE TEMP
CONTROL



WIDE VOLTAGE
RANGE 190-240V



SOFT START UP



FULL SIZE



REMOTE CONTROL
/ SOFT TOUCH



FILTER CLEAN
INDICATOR



EASY FILTER REMOVAL



ECO-FRIENDLY
REFRIGERANT

The Soul of our cooling capabilities
is now Eco-friendly...



Saves as much as 60%
in energy costs...



SILENT

One of the *quietest*
window type airconditioners...

PRODUCT SPECIFICATIONS

WINDOW TYPE INVERTER	KAG-110RSINV	KAG-150RSINV	KAG-200RSINV	KAG-240RSINV
Nominal Capacity	1 hp	1.5 hp	2 hp	2.4 hp
Cooling Capacity	4,477-10,845 kJ/h	6,210-15,042 kJ/h	8,447-20,462 kJ/h	10,560-25,577 kJ/h
Power Supply	1 PH / 230 V / 60 Hz			
Current	1.5 - 4.1 A	2 - 5.9 A	2.7 - 9.1 A	3.4 - 10.1 A
Power	300-950 W	430-1,355 W	610-1,860 W	800-2,340 W
EER	14.9-11.4	14.4-11.1	13.8-11.0	13.2-10.9
Area (Unloaded Space)	13-19 sq. m	20-25 sq. m	26-32 sq. m	33-40 sq. m
Unit Weight (Net/Gross)	43 / 46 kg	50 / 54 kg	55 / 60 kg	60 / 65 kg
Refrigerant Charge (g) R-32	550	630	610	840
Unit Dimension (W*D*H) (mm)	560x700x375	660x700x428	660x800x428	660x800x428
Unit Dimension (W*D*H) (inches)	22x28x15	26x28x17	26x32x17	26x32x17
Package Dimension (W*D*H) (mm)	620x803x410	736x790x490	890x739x505	890x739x505
Package Dimension (W*D*H) (inches)	24x32x16	29x31x19	35x29x20	35x29x20

* Product features and specifications are subject to change without prior notice



LATEST TECHNOLOGY



SUPREME PERFORMANCE