


WINDOW TYPE AIRCONDITIONER



E-SERIES - MECHANICAL

KAG-60DME KAG-80DME
KAG-100DME KAG-190DME KAG-250DME



E-SERIES - REMOTE CONTROLLED

KAG-80DRE KAG-100DRE
KAG-150DRE KAG-190DRE



S-SERIES

KAG-120RS KAG-160RS
KAG-210RS KAG-260RS



S-SERIES INVERTER

KAG-110RSINV
KAG-150RSINV

E-SERIES	KAG-60DME	KAG-80DRE KAG-80DME	KAG-100DRE KAG-100DME	KAG-150DRE KAG-150DME	KAG-190DRE KAG-190DME	KAG-250DME
Rating Capacity (hp)	0.6	0.8	1	1.5	1.9	2.5
Cooling Capacity (kJ/h)	6,750	8,000	10,000	12,995	18,390	24,600
Area (Unloaded Space)	9-11 m ²	12-15 m ²	16-19 m ²	20-24 m ²	25-31 m ²	32-41 m ²
Rated Voltage	230V / 60 hz	230V / 60 hz	230V / 60 hz	230V / 60 hz	230V / 60 hz	230V / 60 hz
Rated Current (A)	2.64	3.4	4.4	5.1	7.5	10.5
Rated Power (w)	626	727	909	1181	1735	2435
EER	10.8	11	11	11	10.6	10.1
Net Weight(kg)	20	31	42	45	52	68
Refrigerant Charge(g)	R-22 / 350g	R-22 / 550g	R-22 / 450g	R-22 / 530g	R-22 / 640g	R-22 / 1,400g
Unit Dimension (WxDxH) (mm)	472 x 400 x 324	450 x 580 x 350	560 x 618 x 375	560 x 618 x 375	660 x 705 x 430	660 x 775 x 430

S-SERIES	KAG-120RS	KAG-160RS	KAG-210RS	KAG-260RS
Rating Capacity (hp)	1.2	1.6	2.1	2.6
Cooling Capacity (kJ/h)	11,200	14,800	19,900	26,200
Area (Unloaded Space)	9-21 m ²	22-26 m ²	27-33 m ²	34-45 m ²
Rated Voltage	230V / 60 hz	230V / 60 hz	230V / 60 hz	230V / 60 hz
Rated Current (A)	4.4	5.6	7.8	11
Rated Power (w)	960	1,240	1,715	2,520
EER	11.7	11.9	11.6	10.4
Net Weight(kg)	43	54	60	64.5
Refrigerant Charge(g)	R-22 / 680g	R-22 / 710g	R-22 / 930g	R-22 / 1,050g
Unit Dimension (WxDxH) (mm)	560 x 618 x 375	660 x 700 x 428	660 x 770 x 428	660 x 770 x 428

S-SERIES INVERTER	KAG-110RSINV	KAG-150RSINV
Rating Capacity (hp)	1	1.5
Cooling Capacity (kJ/h)	9,950	13,800
Area (Unloaded Space)	13-19 m ²	20-25 m ²
Rated Voltage	230V / 60 hz	230V / 60 hz
Rated Current (A)	3.5	4.9
Rated Power (w)	760	1,078
EER	13.1	12.8
Net Weight(kg)	43	50
Refrigerant Charge(g)	R-32 / 550g	R-32 / 630g
Unit Dimension (WxDxH) (mm)	560 x 708 x 375	660 x 700 x 428

* Product features and specifications are subject to change without prior notice

KAG-200RS INV R40 R5 / INV
660 x 800 x 428 mm