

FLOOR / CEILING (REGULAR)



KSG-36C1M



KSG-36C1T



FLOOR / CEILING (INVERTER)

KSM-300C1EINV KSM-400C1EINV



KSM-60CL1T



KSM-60CL1S

PRODUCT SPECIFICATION

FLOOR CEILING SPLIT TYPE	REGULAR				INVERTER	
	KSG-36C1M	KSG-36C1T	KSM-60CL1T	KSM-60CL1S	KSM-300C1EINV	KSM-400C1EINV
Cooling Capacity (kj/h)	37,980	37,980	63,300	63,300	26,375	9,020-41,000
Rated Voltage	230 Volts/60Hz					
Power (W)	3,880	3,350	6,130	6,038	2,280	3,520
EER (kJ/hW)	9.8	11.3	10.3	10.5	11.6	10.8
INDOOR UNIT						
Unit Dimension (W*D*H) (mm)	1285x200x660	1285x200x660	1670x240x680	1670x240x680	1280x660x203	1280x660x203
OUTDOOR UNIT						
Unit Dimension (W*D*H) (mm)	895x330x860	554x554x636	710x710x843	900x340x1167	990x354x966	900x345x965
Copper Tube Size						
Low Side:	ø3/4"	ø3/4"	ø3/4"	ø3/4"	ø3/8"	ø5/8"
High Side:	ø3/8"	ø1/2"	ø3/8"	ø3/8"	ø5/8"	ø3/8"
Maximum Pipe Distance bet. Indoor and Outdoor						
Height:	10 m	10 m	10 m	10 m	10 m	10 m
Length:	30 m	30 m	30 m	30 m	30 m	30 m

* Product features and specifications are subject to change without prior notice