



CEILING CASSETTE

INVERTER^{❄️❄️❄️} Air Conditioner



360 degrees of chill:
Air conditioning redefined.

Up to **5.24**



5-Star CSPF Rating



INVERTER^{❄️❄️❄️}



360°
AIR DISCHARGE



As low as
47dB(A)
*As quiet as library



CEILING CASSETTE

INVERTER Air Conditioner

Introducing Kolin' latest Ceiling Cassette Inverter redefines air conditioning with its **360° degrees air discharge** and ensures uniform cooling distribution throughout the room, eliminating warm spots and maintaining consistent comfort levels from floor to ceiling while ensuring lower costs on electricity bills with its **5-star CSPF rating**, **DC inverter technology**, and **high cooling capacity**.

Embrace the comfortable and quiet environment with the Ceiling Cassette and protect the environment with its zero-ozone-depletion **R32 refrigerant**.

Enjoy comfortable and smooth cooling and save on electricity bills with Kolin's Ceiling Cassette Inverter air conditioner.

PRODUCT SPECIFICATION

MODEL (INDOOR)	KLM-IS40-AA1M32-I	KLM-IS60-AA1M32-I
Nominal Capacity	3 TR / 4.0 hp	5 TR / 6.0 hp
Cooling Capacity	37,980 (11,394 - 41,778) kJ/h	55,503 (15,562 - 60,346) kJ/h
Power Supply	1 Ph / 230 V / 60 Hz	1 Ph / 230 V / 60 Hz
Power Input (Cooling)	3,184 (637 - 3,821) W	5,306 (1,061 - 6,690) W
Input Current (Cooling)	15 A	25 A
CSPF Rating	5.24	n/a
Star Rating	★★★★★	n/a
Refrigerant (Type/Charge)	R32 / 1,450 g	R32 / 2,650 g
Area (Unloaded Space)	51 - 65 m ²	66 - 96 m ²
Airflow (Hi/Mi/Lo)	1950 / 1700 / 1500 m ³ /h	2100 / 1800 / 1500 m ³ /h
Sound Level (Hi/Mi/Lo)	56 / 52 / 47 dB(A)	55 / 51 / 48 dB(A)
Unit Dimension Indoor (WxDxH)	830 x 830 x 245 mm	830 x 830 x 287 mm
Front Panel Dimension (WxDxH)	950 x 950 x 55 mm	950 x 950 x 55 mm
Indoor Packaging Dimension (WxDxH)	910 x 910 x 290 mm	910 x 910 x 330 mm
Front Panel Packaging Dimension (WxDxH)	1035 x 1035 x 90 mm	1035 x 1035 x 90 mm
Unit Weight (Net/Gross)	27.8 / 32.7 kg	29.8 / 35.1 kg
MODEL (OUTDOOR)	KLM-IX40-AA1M32-O	KLM-IX60-AA1M32-O
Unit Dimension (WxDxH)	890 x 342 x 673 mm	946 x 410 x 810 mm
Package Dimension (WxDxH)	995 x 435 x 750 mm	1090 x 500 x 885 mm
Unit Weight (Net/Gross)	43.9 / 47.1 kg	63.9 / 68.9 kg
Copper Tube Size		
High Side/Low Side	Ø 3/8" / Ø 5/8"	Ø 3/8" / Ø 5/8"
Maximum Pipe Distance Between Indoor and Outdoor		
Height/Length/Circuit Breaker	20m / 30m / 40A	30m / 50m / 60A

*Product features and specifications are subject to change without prior notice.
 **All 5 TR Ceiling Cassette air conditioner is exempted on CSPF and Star rating since it is only applicable to 50,400 kJ/h below.
 ***For maximum energy savings and for better health, ideal temperature setting is between 23°C - 25°C
 ****The 47 db(A) is only applicable to KLM-IS40-AA1M32 3TR.

PRODUCT FEATURES




5-Star CSPF Rating



Inverter



R32 Low GWP Refrigerant



Quiet Operation



Self Diagnosis



Built-in Drain Pump



Wide Voltage Range (187-260V)



360° AIR DISCHARGE

SERVICE CENTERS

MAKATI OFFICE

Kolin Bldg.
1854 Sta. Rita St., Guadalupe
Nuevo, Makati City, 1212
(632) 8852 - 6868

PAMPANGA

LRK Commercial Bldg., Jose
Abad Ave., Lagundi Mexico,
Pampanga
(045) 455 - 2934

DAGUPAN

Unit #1 107 Caranglaan
District, Dagupan City
Pangasinan
(075) 529 - 0587

BACOLOD

Door #A-2 & A-3 UTC Bldg.,
Alunan St., Brgy. 36,
Bacolod City
(034) 466 - 9145

ILOILO

Door #4, 5 & 7, D' Appliance
Arcader, South Fundidor,
Molo, Iloilo City
(033) 337 - 5314

CEBU

Lot 758-B-1, P. Suico St.,
Upper Tabok, Mandaue,
Cebu City
(032) 234 - 1844

DAVAO

Blk 17 Lot 9, Calamansi St.,
Juna Subd., Matina,
Davao City
(082) 227 - 0048

CAGAYAN DE ORO

Door #3 De Oro Land Bldg.,
Julio Pacana St., Puntod,
Cagayan de Oro City
(088) 557 - 7353



OVER 220 AUTHORIZED SERVICE CENTERS NATIONWIDE

Exclusively Distributed by Kolin Philippines International, Inc.

Visit our website:

www.kolinphil.com.ph

Follow our Social Media:

[Facebook](#) [Instagram](#) [YouTube](#) [Twitter](#) [LinkedIn](#) [Kolin Philippines](#)

VRSN00 022024