



FLOOR/CEILING

INVERTER^{❄️❄️❄️} Air Conditioner

*A breeze of flexible and efficient
air conditioning, tailored for you.*



INVERTER^{❄️❄️❄️}



FLOOR/CEILING

INVERTER Air Conditioner

Kolin's Floor/Ceiling Inverter is designed to provide maximum cooling performance with outstanding versatility and a space-saving solution suitable for ceiling and floor installation. With a **higher CSPF rating of up to 4.92**, a **5-star rating**, and **DC Inverter Technology**, you can save energy and reduce your electricity bills while promoting an eco-friendly, cost-effective, and safer environment with its **R32 refrigerant**.

The combination of its **4-way air flow** and **strong air flow** features quickly spreads cool air that can reach the farthest end of the room, ensuring even, cool, and comfortable air distribution.

Level up to a more comfortable environment that offers serenity, versatility and peace of mind with Kolin's newest Floor/Ceiling Inverter air conditioner.



PRODUCT FEATURES




5-Star CSPF Rating



Inverter



R32 Low GWP Refrigerant



Quiet Operation



Strong Air Flow



4-Way Air Flow



Left or Right Drain Position



Self Diagnosis



Wide Voltage Range (187-260V)

Indoor Unit



*3 TR / 4.0 hp



*5 TR / 6.0 hp

Outdoor Unit



*3 TR / 4.0 hp



*5 TR / 6.0 hp

Versatile Installation



Floor Installation



Ceiling Installation

PRODUCT SPECIFICATION

MODEL (INDOOR UNIT)	KLM-IC40-AA1M32-I	KLM-IC60-AA1M32-I
Nominal Capacity	4.0 hp / 3 TR	6.0 hp / 5 TR
Cooling Capacity	37,980 kJ/h (11,394-41,778)	55,503 kJ/h (15,562-60,346)
Power Supply	1 Ph / 230 V / 60 Hz	1 Ph / 230 V / 60 Hz
Power Input	3,184 (637-3,821) W	5,306 (1,061-6,367) W
Input Current	15 A	25 A
CSPF Rating	4.92	n/a
Star Rating	★★★★★	n/a
Refrigerant (Type/Charge)	R32 / 1,450 g	R32 / 2,650 g
Area (Unloaded Space)	51 - 65 m ²	66 - 96 m ²
Airflow (Hi/Mi/Lo)	1900 / 1600 / 1400 m ³ /h	2400 / 2100 / 1900 m ³ /h
Sound Level (Hi/Mi/Lo)	55 / 51 / 47 dB(A)	57 / 54 / 52 dB(A)
Unit Dimension (WxDxH)	1285 x 675 x 235 mm	1650 x 675 x 235 mm
Packaging Dimension (WxDxH)	1360 x 755 x 318 mm	1725 x 755 x 318 mm
Unit Weight (Net/Gross)	32 / 38 kg	42 / 49.1 kg
MODEL (OUTDOOR UNIT)	KLM-IX40-AA1M32-O	KLM-IX60-AA1M32-O
Unit Dimension (WxDxH)	890 x 342 x 673 mm	946 x 410 x 810 mm
Packaging Dimension (WxDxH)	995 x 435 x 750 mm	1090 x 500 x 885 mm
Unit Weight (Net/Gross)	43.9 / 47.1 kg	63.9 / 68.9 kg
Copper Tube Size		
High Side/Low Side	Ø 3/8" / Ø 5/8"	Ø 3/8" / Ø 5/8"
Maximum Pipe Distance Between Indoor and Outdoor		
Height/Length/Circuit Breaker	20m / 30m / 40A	30m / 50m / 60A

*Product features and specifications are subject to change without prior notice.

**For maximum energy savings and for better health, ideal temperature setting is between 23°C - 25°C.

***All 5 TR Floor/Ceiling air conditioner is exempted on CSPF and Star rating since it is only applicable to 50,400 kJ/h below.

****The 47 db(A) is only applicable to KLM-IC40-AA1M32 3TR.

SERVICE CENTERS

MAKATI OFFICE

Kolin Bldg.
1854 Sta. Rita St., Guadalupe
Nuevo, Makati City, 1212
(632) 8852 - 6868

ILOILO

Door #4, 5 & 7, D' Appliance
Arcader, South Fundador,
Molo, Iloilo City
(033) 337 - 5314

PAMPANGA

LRK Commercial Bldg., Jose
Abad Ave., Lagundi Mexico,
Pampanga
(045) 455 - 2934

CEBU

Lot 758-B-1, P. Suico St.,
Upper Tabok, Mandaue,
Cebu City
(032) 234 - 1844

DAGUPAN

Unit #1 107 Caranglaan
District, Dagupan City
Pangasinan
(075) 529 - 0587

DAVAO

Blk 17 Lot 9, Calamansi St.,
Juna Subd., Matina,
Davao City
(082) 227 - 0048

BACOLOD

Door #A-2 & A-3 UTC Bldg.,
Alunan St., Brgy. 36,
Bacolod City
(034) 466 - 9145

CAGAYAN DE ORO

Door #3 De Oro Land Bldg.,
Julio Pacana St., Puntod,
Cagayan de Oro City
(088) 557 - 7353



OVER 220 AUTHORIZED SERVICE CENTERS NATIONWIDE

Exclusively Distributed by Kolin Philippines International, Inc.

Visit our website:

www.kolinphil.com.ph

Follow our Social Media:

[Facebook](#) [Instagram](#) [YouTube](#) [Twitter](#) [LinkedIn](#) [Kolin Philippines](#)

VRN00 022024