



TEST REPORT

Basic Information	
Model No.	GWC30AVEXF-S6DNA1A (KS-IW30-GPAI13P1M32)
Power supply Applied	220-240V 60Hz
Cooling Capacity	8000W
Heating Capacity	---W
Power Input (C/H)	2666W/---W
Refrigerant (kg)	R32, 0.9
Compressor Model	QXFS-M238zX070
Fan Motor Model (Indoor unit)	F70B
Fan Motor Model (Outdoor unit)	B-LW120R-L-ZL(10P)
Applicable Standard No.	ISO 5151-2017

Basic Test Result						
No.	ITEM	TEST RESULT				REMARK
1	Cooling Capacity	Rated cooling capacity	Inter cooling capacity	Intermediate low-temperature refrigerating capacity	CSPF	---
	Power supply Applied (V)	228.7	230.4	230.6	6.06	PASS
	Entering Air D.B.T (I) (°C)	27.02	27.04	27.02		
	Entering Air W.B.T (I) (°C)	19.00	19.02	19.01		
	Entering Air D.B.T (O) (°C)	35.00	35.02	28.99		
	Entering Air W.B.T (O) (°C)	19.90	19.73	16.65		
	Cooling capacity(W)	7832	4050	4092		
	Cooling Power input(W)	2358	861	656		
	EER	3.32	4.70	6.24		



Other Test Result :

1	Max. cooling performance test	/
2	Min. cooling ,freeze-up air blockage performance tests	/
3	Condensate control and enclosure sweat performance test	/
4	Freeze-up drip performance test	/
5	Max. heating performance test	/
6	Min. heating performance test	/
7	Automatic defrost performance test	/

Note :

“---” in chart stands for “not applicable” .

Tested By : YueQiuLi

Reviewed By:LiuZhao

Approved By: HouKaiZe